



SIMATIC S7-1200, Analog input, SM 1231 TC, 4 AI thermocouples

Figure similar

General information	
Product type designation	SM 1231, AI 4x16 bit TC
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption, typ.	40 mA
from backplane bus 5 V DC, typ.	80 mA
Power loss	
Power loss, typ.	1.5 W
Analog inputs	
Number of analog inputs	4; Thermocouples
permissible input voltage for voltage input (destruction limit), max.	±35 V
Technical unit for temperature measurement adjustable	Degrees Celsius/degrees Fahrenheit
Input ranges	
• Voltage	Yes
• Current	No
• Thermocouple	Yes; J, K, T, E, R, S, N, C, TXK/XK(L); voltage range: ±80 mV
• Resistance thermometer	No
• Resistance	No
Input ranges (rated values), voltages	
• -80 mV to +80 mV	Yes
— Input resistance (-80 mV to +80 mV)	≥1 MOhm
Input ranges (rated values), thermocouples	
• Type B	Yes
• Type C	Yes
• Type E	Yes
• Type J	Yes
• Type K	Yes
• Type N	Yes
• Type R	Yes
• Type S	Yes
• Type T	Yes
• Type TXK/TXK(L) to GOST	Yes
Thermocouple (TC)	
Temperature compensation	
— parameterizable	No
Analog value generation for the inputs	
Measurement principle	integrating

Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> Resolution with overrange (bit including sign), max. Integration time, parameterizable Interference voltage suppression for interference frequency f_1 in Hz 	15 bit; + sign No 85 dB at 50 / 60 / 400 Hz
Smoothing of measured values	
<ul style="list-style-type: none"> parameterizable 	Yes
Errors/accuracies	
Temperature error (relative to input range), (+/-)	25 °C ±0.1%, to 55 °C ±0.2% total measurement range
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.5 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, $f_1 =$ interference frequency	
<ul style="list-style-type: none"> Common mode interference, min. 	120 dB
Interrupts/diagnostics/status information	
Alarms	Yes
Diagnostics function	Yes; Can be read out
Alarms	
<ul style="list-style-type: none"> Diagnostic alarm 	Yes
Diagnoses	
<ul style="list-style-type: none"> Monitoring the supply voltage Wire-break 	Yes Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> for status of the inputs for maintenance 	Yes Yes
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
Ambient conditions	
Free fall	
<ul style="list-style-type: none"> Fall height, max. 	0.3 m; five times, in product package
Ambient temperature during operation	
<ul style="list-style-type: none"> min. max. horizontal installation, min. horizontal installation, max. vertical installation, min. vertical installation, max. 	-20 °C 60 °C -20 °C 60 °C -20 °C 50 °C
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> min. max. 	-40 °C 70 °C
Air pressure acc. to IEC 60068-2-13	
<ul style="list-style-type: none"> Operation, min. Operation, max. Storage/transport, min. Storage/transport, max. 	795 hPa 1 080 hPa 660 hPa 1 080 hPa
Relative humidity	
<ul style="list-style-type: none"> Operation at 25 °C without condensation, max. 	95 %
Pollutant concentrations	
<ul style="list-style-type: none"> SO₂ at RH < 60% without condensation 	SO ₂ : < 0.5 ppm; H ₂ S: < 0.1 ppm; RH < 60% condensation-free
connection method	
required front connector	Yes
Mechanics/material	
Enclosure material (front)	

• Plastic

Yes

Dimensions

Width	45 mm
Height	100 mm
Depth	75 mm

Weights

Weight, approx.	180 g
-----------------	-------

last modified:

8/23/2023 